

NEW-85XX010



Newlink PG Hanger Kits

- The kit includes: Hanging bar (1) / Rods (2) Anchor bolt (2) / Nut (4)
- Electro Zinc Resistant Finish
- NEC Approved
- NEWMAX-25 Year Certification available (*)

Technical Specifications:

Steel	(Min. Yield = 33KSI) (35 KSI for Stainless)			
Plain	Hot rolled pickled and oiled steel per ASTM A569 or A570			
Pre-Galvanized	Mill galvanized steel per ASTM A653 CS or SS G90			
Hot Dip Galvanized After	Plain steel which is hot dipped after fabrication per ASTM A123			
Fabrication				
Stainless Steel	Type 304 or 316L fully annealed stainless steel			
NEC Permitted (types of cables)	 Power and Control Tray Cable (Type TC) - NEC Article 336 Power Limited Tray Cable (Type PLTC) - NEC Sections 725-61© and 725.82(E) Instrument Tray Cable (Type ITC) - NEC Article 727 Optical Fiber Cables - Article 770 Fire Alarm Circuit Conductors - Article 760 Communication Cables - Article 800 Mineral Insulated (MI)Cable - Article 332 Metal Clad (MC) Cable - Article 330 			





Ordering Information:

P/N	Description	Includes	Set	Finish
NEW-8504010	Hanger-10 Kit for 4"	Hanging bar (1) / Rods (2) (38.5") Anchor bolt (2) / Nut (4)	1	Galvanized
NEW-8506010	Hanger-10 Kit for 6"	Hanging bar (1) / Rods (2) (38.5") Anchor bolt (2) / Nut (4)	1	Galvanized
NEW-8508010	Hanger-10 Kit for 8"	Hanging bar (1) / Rods (2) (38.5") Anchor bolt (2) / Nut (4)	1	Galvanized
NEW-8512010	Hanger-10 Kit for 12"	Hanging bar (1) / Rods (2) (38.5") Anchor bolt (2) / Nut (4)	1	Galvanized

^(*) NEWMAX-25 Year Certification applies when a complete Newlink Cabling Channel is installed.