

CAT-6A Patch Cords CMR Rated



Features:

- Exceeds ANSI/TIA/EIA 568-C.2
- Exceeds ISO/IEC 11801 CLASS E_A
- Stranded 24 AWG UTP CMR Rated
- Universal Wiring T568A/B
- 500 MHz Factory Tested
- Superior Performance

Technical Specifications:

NEWLINK patch cords meet the communication's most stringent requirements and exceed them with enhanced technical characteristics. Flexibility, resilience, perfect geometry matching, gold plated contacts, fire-retardant jacket, low resistance copper stranded conductors and many other details are the base for this product series. Available in attractive colors for easy identification. Most used lengths available from stock. Special dimensions available upon request, minimum orders apply.

- 4-pair straight universal termination
- Exceeds TIA/EIA 568-C.2-2 CAT6A performance
- Exceeds ISO/IEC 11801 Class E_A
- Very low Insertion Loss
- Superior Extra NEXT and ACR Headroom
- 24 AWG stranded UTP construction
- CMR Rated jacket
- Meets TIA-968-A and IEC 60603-7
- 50 micro-inches gold plated contacts
- Excellent bend relief colored boots
- Available colors: blue, gray, red, green, and yellow
- Available lengths: 1, 2, 3, 4, 7 and 10 feet

Supported Applications:

- Voice, Fax, T1, ISDN
- 10BASE-T
- 100BASE-TX, 100BASE-T4, 100VG-AnyLan
- ATM-25, ATM-51, ATM-155
- 1000BASE-T
- 10 GIGA



NEWLINK

Cabling Systems

NEW-177xyy

Ordering Information:

- **NEW-177xyy** Category 6A Patch cable, CMR Rated,

Where: **xx**= length in feet
yy= color (BL = blue, GY = Grey, RD = Red, GN = Green, YW = Yellow)